

Technical Data Sheet

Capatue™ SCA-E87F

Abstract

SCA-E87F is a versatile epoxy organo-reactive silane with two hydrolysable ethoxy groups suitable for use as adhesion promoters in polysulfide, urethane, epoxy and acrylic caulks sealants and adhesives, especially suitable to be used as adhesion promoter and crosslinker for waterborne adhesives and sealants.

Chemical Name

(3-Glycidioxypropyl)methyldiethoxysilane

Synonyms

Diethoxy(3-glycidioxypropyl)methylsilane;
 [3-(2,3-Epoxypropoxy)propyl]diethoxymethylsilane

CAS Registry Number

2897-60-1


EINECS

220-780-8

Molecular Formula

$C_{11}H_{24}O_4Si$

Molecular Structure



Molecular Weight

248.39

Equivalents

Product	Supplier
WetLink 78	Momentive (formerly OSi Specialties)
Z-6042	Dow Corning
GENIOSIL® GF 84	Wacker
KBM-402	Shin-Etsu

**Typical Properties**

Index	Value
Appearance	Colorless, transparent liquid
Purity (GC), %	≥ 97
Specific Gravity (ρ_{20}), g/cm ³	0.98
Flash Point, °C	121
Solubility	Soluble in acidified water after hydrolysis, alcohol, acetone, and most aliphatic esters at normal application levels fewer than 5%. Hydrolysis releases ethanol.

Applications and Performance

1. Can be used in place of 3-Glycidoxypropyltrimethoxysilane (SCA-E87M) in many applications, It will generates ethanol upon hydrolysis [which is a volatile organic compound (VOC) but is not a hazardous air pollutant (HAP)] while SCA-E87M generates methanol upon hydrolysis which is both a VOC and a HAP.
2. SCA-E87F silane can be employed as an adhesion promoter or crosslinker. It may be suitable for use as a water stable single component crosslinker. In such applications, SCA-E87F silane should provide a means of replacing a 2 part waterborne adhesive with a single component system. The benefits of a silane crosslinked water stable single component system include reduced scrap, improved process efficiency and reduced crosslinker toxicity.

Packing

The regular packing of this product is 25kg plastic pail, 200L steel drums and 1000L immediate bulk container.

Storage and Shelf Life

Should be stored in dry, cool, ventilated room; keep away from water, moisture, high temperature and fire. This product has a shelf life of at least 12 months if stored in tightly closed original container at room temperature.
If this product is kept beyond the shelf life recommend on the product label, it is not necessarily unusable, but a quality control should be performed on the properties relevant to the application.

Product Safety and Handling

When considering the use of any Capatue products in a particular application, you

[Http://www.capatue.com](http://www.capatue.com) E-mail: info@capatue.com

Tel: +86-25-8637 1192, 8637 1193 Fax: +86-25-8637 1191 ext. 0

Add: Block E4, Zidong Industry Park, 2 Zidong Road, Maqun Town, Qixia Dist., Nanjing, Jiangsu, China, 210023

should read our latest Material Safety Data Sheets (MSDS) thoroughly for handling instructions, personal protective equipment if necessary, other safety issue and toxicological data as well as for information on proper transportation, storage and use to ensure that the use you intend can be accomplished safely. Our latest Material Safety Data Sheets (MSDS) and other product safety information are available at www.capatue.com or upon request, from our customer service department.

Use of other material in conjunction with Capatue products may require addition precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

This product is for industry use only; it is neither tested nor represented as suitable for food, medical or pharmaceutical uses.

Limited Warranty Information

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Capatue's products are safe, effective, and fully satisfactory for the intended end use.

Suggestions of use shall not be taken as inducements to infringe any patent.

Capatue's sole warranty is that the product will meet the Capatue sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Capatue specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Capatue disclaims liability for any incidental or consequential damages.

Customer must do enough tests before their regular production to ensure that our product is suitable for their specific application.